

Floor Sealer Finish #7

Floor Finish

Description

Floor Sealer Finish #7 produces a tough coating that provides excellent gloss, durability and resistance to dirt embedment and scuff marking. The formula is based on new generation polymer technology designed to provide superior performance with long-lasting results. Floor Sealer Finish dries to form a colourless, tough modified acrylic / metal cross-linked film which has an outstanding gloss level and a very high degree of scratch repair when burnished. It is perfect for a variety of surfaces and is ideal for floors with high traffic numbers.

Features and Benefits

- Ideal for the following floors: VCT, terrazzo, concrete, marble, quarry tile. Not recommended for outdoor use. Designed for high traffic areas.
- High gloss, ultra-durable, ultra-high speed finish. Excellent presentation and response to UHS burnishing.
- Excellent for prestige floors and all busy floors, including shopping centres, hospitals and commercial buildings.
- High solids resulting in maximum durability. Requires fewer coats saving time and labour.
- Provides an excellent clear gloss with optical brightener technology which delivers advanced brightness.
- Prevents scuffing and black heel marking.
- Easy to apply and recoat increasing speed and efficiency.
- Superior floor coverage and fast drying time..
- Excellent resistance to isopropyl alcohol and detergent solutions.
- Features low ammonia and acrylic odour; recommended for hospitals.
- Meets industry slip rating of 0.40.

Product Specifications & Information

Appearance:	Off-White Emulsion
pH:	8.0 – 9.5
Viscosity, cps	<200
% Solids	22% w/w
Dry Time:	Allow at least 30 minutes depending on weather conditions.

Coverage: 55-60m²/L
Slip Rating 0.40

Use Directions

Prior to application of Floor Sealer Finish, floors must be adequately stripped with Floor Stripper, rinsed thoroughly and allowed to completely dry.

Initial Application

Apply 3-4 thin coats. Allow floors to thoroughly dry between coats and prior to burnishing. DO NOT apply more than 4 coats in a 24 hour period.

Optional for old porous floors and heavy traffic areas: Apply 2 thin coats of Floor Base Sealer #6, then apply 4 coats of Floor Sealer Finish #7.

Maintenance

For a floor that has been deep cleaned or scrubbed, allow to dry thoroughly. Apply 1-2 thin coats. Allow floor to dry thoroughly between coats and prior to burnishing.

Buffing and Burnishing

Floor Sealer Finish #7 is ideal for use in no-buff or buffing programs using all speeds of buffing or burnishing machines. For spray buffing, mop-on or auto-scrubber restoring use in conjunction with Floor Maintainer (combined floor cleaner and polish maintainer).

Storage

This product should be stored under cover, out of direct sunlight and avoiding extreme temperature changes.

Safety Information

Floor Sealer Finish #7 is classified as NON HAZARDOUS according to the criteria of Safe Work Australia and is classified as a NON DANGEROUS GOOD according to the Australian Dangerous Goods Code.

Refer to our safety data sheet (SDS) for more information or consult your Wirrpanda Supplies representative for further assistance.

Packages

3 x 5L